




West Coast Supplies
Innovative Packaging Solutions

ROTOPLAT 508

SEMI-AUTOMATIC STRETCH WRAPPER

The Rotoplat 508's intuitive seven (7) inch color touchscreen makes it easy to set up the correct parameters for wrapping each of your loads. You control containment force, rotation speed, roping and banding at nine (9) levels on each load.

- Save 30-55% on film with Cube Technology
- Rconnect ready
- Save 12 unique load configurations
- 65" turntable with 28 support bearings
- 4400 lbs. weight capacity
- 110" standard wrap height





Performance features:



R-CONNECT READY

Developed to provide usage and performance data via the cloud. Utilization drastically reduces downtime by giving you informational transparency, allowing you to connect with your machines remotely to investigate

COLOR TOUCH SCREEN

The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the MULTILEVEL CONTROL function.



PDS CARRIAGE

PDS Carriage with dual pre-stretch rollers controlled via the control panel. Pre-stretch system stretch ratio adjustable from panel board up to 250%. "Stretch Control" control activates the electromagnetic clutch positioned on the first roller making pre-stretch variable from 0%-250%.



Rotoplat 508 Specifications

Performance Criteria

Production Speed:

Up to 40 LPH

Turntable Speed:

5 – 12 RPM

Turntable Drive:

1 HP VAC

Load Handling System

Turntable Size:

65" Diameter

Maximum Load Height:

110"

Maximum Load Weight:

4400 lbs.

Film Delivery System

- Standard Pre-stretch: Variable 0 – 250%
- Containment Force: Multi-Level Variable
- Film Carriage Motor: ½ HP VAC
- Height Sensing: Automatic via photocell
- Film Threading: Patented S-Pattern
- Corner Compensation: Load Cell

Safety Features

- Anti-fall device on carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

Utilities

Voltage:

115V, 20 amps, 60 Hz, 1 PH

Warranty:

5 Years