



Performance features:



CLAMP, CUTTING AND WELDING UNIT

Ensure a perfect adherence of the film to the load for better containment with the cut, clamp, and welding system (CW). The new aluminum clamp controlled by a pneumatic cylinder holds the film clearly and without slippage during cutting.

COLOR TOUCH SCREEN

The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the MULTILEVEL CONTROL function.



PVS CARRIAGE Powered stretch s

Powered stretch system controlled by two motors. Stretch ratio adjustable from panel board from 150-400%. Force to the load controlled by patented electronic device and adjustable from panel board.



Rconnect standard, a

technologically advanced monitoring system combines innovation and connection, allowing complete control of the operation of the machines and a total support to the final customer. Monitor and improve your performance with remote assistance.



Remote Control

The remote control comes standard with the Technoplat and can control up to 4 units.



Performance Criteria

Production Speed:

Up to 40 LPH

Turntable Speed:

5 - 15 RPM

Turntable Drive:

1 HP VAC

Load Handling System

Turntable Size:

65" Diameter

Maximum Load Dimensions:

52" W x 52" L x 110" H

Maximum Load Height:

110" Standard

Maximum Load Weight:

4400 lbs.

Film Delivery System

- Multi-Level Variable 100 400%
- · Containment Force: Variable Load Cell
- Film Carriage Motor: 1/2 HP VAC Chain Driven
- · Height Sensing: Automatic via photocell
- Film threading: Patented S-Pattern
- · Corner Compensation: Load Cell
- Standard Film Width 20" (30" option)

Safety Features

- · Anti-Fall Device on Carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

Hardware

Voltage:

110V, 20 AMP, 60 Hz, 1 PH

Air:

60 PSI

NEMA 12 Enclosure

Standard

2750 Mercantile Drive, Suite 100 Rancho Cordova, CA 95742 Phone 916-852-6675 Fax 916-852-6676 www.westcoastsupplies.com